



7400 SW Cherry Drive  
Portland, OR 97223-8041 USA

PH: (800) 842-1990

Fax: (503) 608-3939

## SYLVAN **BBO&ES** PLYWOOD CONCRETE FORMING PANELS

Sylvan's BBO&ES is concrete forming panel ALL Group 1, Structural 1 wood species throughout and are made to with stand high loads.

This structural wood panel is fully sanded front and back with smooth wood B Grade Face, and B Grade back with inner plies cross-banded for strength. Mill applied release agent facilitates ease of stripping and cleaning. Edges are sealed to resist water absorption.

### **General product information:**

#### **Product description:**

Sanded natural wood surface panel Group 1, Struct 1 designed for concrete form work for durability and multiple pours.

#### **Surface:**

Sanded B Grade Face and Back with mill applied protective Form release agent and Edge sealed exterior water resistant phenolic glue.

#### **Applications:**

Residential, Commercial, and Institutional infra-structural Concrete formwork.

#### **Panel sizes:**

Thickness: 3/4" 7-Ply

4X8: 48"x96"

4X10: 48"x120"

#### **Handling and Storage:**

- Handle with care for maximum reuse and to prevent panel chipping, denting or corner damage.
- Panels must not be stored in contact with the ground.
- Clean forms carefully after stripping.
- Stack face-to face and back-to-back.
- Store in a dry, clean area out of sun and rain, covered loosely to allow for air circulation.

#### **Cleaning and Release Agent Application:**

After removal inspect panels. Clean using a hardwood wedge and stiff fiber brush (metal brush can damage wood fiber surface). Some light tapping on the backside helps release hard dried concrete. Remove nails, holes should be filled with wood patch, or other suitable material. Refinish and lightly treat with a form-release agent before re-using.

*Information on this and other concrete forming products available at:  
[www.sylvan-products.com/concrete](http://www.sylvan-products.com/concrete)*